

# The SWR-368-40

## SPECIFICATIONS

<b>PV Panel</b>	High-Impact Resistant Polycrystalline 40 Watt Panel
<b>Fan Motor</b>	10-24 Volt DC Brushless Motor Double-Shielded Ball Bearings
<b>Fan Decibel</b>	<60dB(A) (at a meter away) Equivalent to an air conditioning unit
<b>Fan Cap</b>	Aluminium alloy for maximum durability
<b>Body</b>	Corrosion Resistant Steel (Suitable for coastal installations)
<b>Flashing</b>	<b>Length &amp; Width:</b> 500mm <b>Height:</b> 0.9mm
<b>Coating</b>	Electro Static UV resistant spray cured in high temperature drying process
<b>Hardware</b>	Cold sheet steel brackets, stainless steel fasteners & screen
<b>Dimensions</b>	<b>Diameter:</b> 600mm <b>Height:</b> 250mm <b>Throat:</b> 368mm
<b>Weight</b>	6KG
<b>Colour</b>	Black powder coating
<b>Options</b>	Fixed Temp Thermostat (30°C) Adjustable Temp Thermostat (10-30°C) Constant Current Module 300mm Adaptor for ducting



The **SWR-368-40** is one of our new units in the SWR range. This particular model is our largest of the new residential range, and suits properties up to 250m<sup>2</sup>, making it a suitable unit for most Australian homes.

The SWR-368-40 has seen use in both residential and commercial applications, making it a truly versatile unit.

