

# The SW-AU-C-110

## SPECIFICATIONS

Airflow Capacity	Up to 7,000m <sup>3</sup> /h (Equivalent to 116,667 litres per minute)
PV Panel	High-Impact Resistant Polycrystalline 110 Watt Panel
Fan Motor	10-24 Volt DC Brushless Motor Double-Shielded Ball Bearings
Fan Decibel	<70dBA (at a metre away) Equivalent to a conversation at 1 metre
Fan Cap	Powder-coated aluminium
Body	Stainless Steel 304
Flashing	Length & Width: 900mm Height: 0.9mm
Coating	Electro Static UV resistant spray cured in high temperature drying process
Hardware	Stainless steel brackets, stainless steel fasteners & mesh
Dimensions	Diameter: 900mm Throat Diameter: 622mm Height: 300mm
Packing Size	Unit: 920mm × 920mm × 340mm PV Panel: 1160mm × 790mm × 70mm
Packing Weight	SW-AU-C110: 15kg PV Panel: 18KG
Colour	Shale Grey fan cap All other parts uncoated (metal finish)
Options	Fixed Temp Thermostat (30°C) Adjustable Temp Thermostat (10-30°C) Constant Current Module



The SW-AU-C-110 is our smaller commercial unit. Despite being 'smaller', this unit is still a powerful fan, capable of extracting up to 7,000m<sup>3</sup>/h.

This unit is ideal for extracting air from spaces such as:

- Garages or workshops,
- Small warehouses,
- Factories.

If you need a dedicated ventilation solution for your business, the SW-AU-C-110 is an ideal ventilator for you.



# The SW-AU-C-155

## SPECIFICATIONS

**Airflow Capacity** Up to 10 000m<sup>3</sup>/h  
(Equivalent to 166,680 litres per minute)

**PV Panel** High-Impact Resistant Polycrystalline  
155 Watt Panel

**Fan Motor** 10-24 Volt DC  
Brushless Motor  
Double-Shielded Ball Bearings

**Fan Decibel** <73dBA (at a metre away)  
Equivalent to a conversation at 1 metre

**Fan Cap** Powder-coated aluminium

**Body** Stainless Steel 304

**Flashing** Length & Width: 900mm  
Height: 0.9mm

**Coating** Electro Static UV resistant spray cured in high  
temperature drying process

**Hardware** Stainless steel brackets, stainless steel  
fasteners & mesh

**Dimensions** Diameter: 900mm  
Throat Diameter: 622mm  
Height: 300mm

**Packing Size** Unit: 920mm × 920mm × 340mm  
PV Panel: 1650mm × 790mm × 70mm

**Packing Weight** SW-AU-C155: 15kg  
PV Panel: 22KG

**Colour** Shale Grey fan cap  
All other parts uncoated (metal finish)

**Options** Fixed Temp Thermostat (30°C)  
Adjustable Temp Thermostat (10-30°C)  
Constant Current Module



The SW-AU-C-155 is our largest commercial ventilation unit.

It is our most popular commercial fan with a capacity of up to 10 000m<sup>3</sup>/h. It is incredibly powerful and an industry-leading model.

This unit is ideal for extracting air from spaces such as:

- Gymnasiums or sporting centres,
- Warehouses,
- Factories
- Agricultural sheds

If you need a dedicated ventilation solution for a large-scale commercial property or business, contact us today to find out more.

